



DESCRIÇÃO:	PROJETO/CONJUNTO:	DES. APROV. ESCALA: 2 DATA: 03/12/2020	TRATAMENTO TÉRMICO: TRATAMENTO SUPERFICIAL:	<table border="1"> <thead> <tr> <th colspan="8">Dimensões sem tolerância: DIN 7168</th> </tr> <tr> <th>Dimensões mm</th> <th>0,5-3,0</th> <th>3,0-6,0</th> <th>6,0-30</th> <th>30-120</th> <th>120-315</th> <th>315-1000</th> <th>1000-2000</th> </tr> </thead> <tbody> <tr> <td>Toler. c/ usinag.</td> <td>±0,1</td> <td>±0,2</td> <td>±0,3</td> <td>±0,5</td> <td>±0,8</td> <td>±1,2</td> <td>±1,2</td> </tr> <tr> <td>Toler. bruta</td> <td>±0,2</td> <td>±0,5</td> <td>±1</td> <td>±1,5</td> <td>±2,0</td> <td>±3,0</td> <td>±4,0</td> </tr> </tbody> </table>	Dimensões sem tolerância: DIN 7168								Dimensões mm	0,5-3,0	3,0-6,0	6,0-30	30-120	120-315	315-1000	1000-2000	Toler. c/ usinag.	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±1,2	Toler. bruta	±0,2	±0,5	±1	±1,5	±2,0	±3,0	±4,0
Dimensões sem tolerância: DIN 7168																																				
Dimensões mm	0,5-3,0	3,0-6,0	6,0-30	30-120	120-315	315-1000	1000-2000																													
Toler. c/ usinag.	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±1,2																													
Toler. bruta	±0,2	±0,5	±1	±1,5	±2,0	±3,0	±4,0																													
NUMERO DO DESENHO: ATUADOR_KTC_LA_J_24_5_100			CLIENTE:	<table border="1"> <thead> <tr> <th colspan="4">Tolerância Ang.</th> </tr> <tr> <th>ATE</th> <th>10mm</th> <th>50mm</th> <th>MAIS</th> </tr> </thead> <tbody> <tr> <td>10mm</td> <td>30'</td> <td>20'</td> <td>10'</td> </tr> </tbody> </table>	Tolerância Ang.				ATE	10mm	50mm	MAIS	10mm	30'	20'	10'																				
Tolerância Ang.																																				
ATE	10mm	50mm	MAIS																																	
10mm	30'	20'	10'																																	