



Automation for a Changing World

Delta Compact Modular Mid-range PLC AS Series



www.deltaww.com



AS Series

AS Series

The AS Series Compact Modular Mid-range PLC is a high performance multi-purpose controller designed for all kinds of automated equipment. It features Delta's self-developed 32-bit SoC CPUs for enhanced execution speed (40k steps/ms) and supports up to 32 extension modules or up to 1,024 inputs/outputs. The AS series provides accurate positioning control for up to 8 axes via CANopen motion network and 6 axes via pulse control (200 kHz). It is widely used in diverse automated equipment such as electronics manufacturing, labeling, food packaging, and textile machines.

The AS Series Controller is equipped with CANopen and EtherNet/IP network communication for high-speed data transmission. The professional yet simple editing software ISPSOFT delivers quick hardware and network configuration with built-in function blocks for different industries. It also provides multi-layer password protection for enhanced system security.

The AS Series adopts a rackless design and patented DIN rail clips for fast vertical module installation. The simple shape and dark gray exterior of the AS series help resist stains and dirt in harsh industrial environments.





High Efficiency Computing

- Advanced CPU performance
- Optimized execution efficiency
- Optimized I/O update rate
- Permanent data backup, no battery required



Accurate Axis Control

- Delta CANopen positioning control
- Simple control instructions
- High-speed pulse positioning control
- High-speed counter



Simple Installation

- Easy installation process
- Convenient grounding protection
- Screwless installation procedure
- Loose-proof clip-type terminal block



Industrial Network Solution

- EtherNet/IP solution
- Remote I/O solution
- Serial communication solution



Programming and Diagnosis Functions

- Modular programming structure
- Convenient editing environment
- Easy hardware configuration and parameter setting
- Complete setting tools
- Multiple password protection



Models and Specifications

- Model name explanation
- CPU
- AS Series I/O modules
- High-density modules and accessories
- Dimensions
- Ordering information

High Efficiency Computing



Delta's self-developed AS Series CPU provides 32-bit high-performance computing. As the core of a high-efficiency controller, it helps increase productivity and adaptability to demanding equipment.



Advanced CPU Performance

■ High speed execution up to 40k steps/ms

(Condition: 40 % LD instruction/60% MOV instruction)

- Max. number of inputs/outputs: 1,024
- Program capacity: 128k steps
- Data registers: 60k words
- Max. extension ability: 32 modules

LD instruction

25 ns

MOV instruction

0.15 μ s

Floating point
operation instruction

1.6 μ s

Trigonometric
function instruction

3.5 μ s




Optimized Execution Efficiency

■ General Scanning Method


Standard simplex scanning which sequentially goes through instructions by fixed schedule operation (e.g. I/O update).

It significantly affects overall execution speed.



■ AS Series Scanning Method


Fixed schedule operations will be automatically processed by CPU background program when scanning starts. It significantly enhances execution speed.



Optimized I/O updates

■ Common in the industry: PLC module bus update via serial communication


- General serial communication: the signal is sequentially sent from the 1st module to the last module. The more modules the longer I/O update time it takes.



■ AS Series: PLC module bus update via parallel communication

- Industrial communication: the signal is sent via parallel communication. The I/O update time is not significantly prolonged even with more modules.


Industrial communication bus greatly enhances stability and speed.



Note: The real updating performance will be different by different extension modules.

Permanent data backup, no battery required

■ Non-volatile memory material for data backup




	PLC power off
PLC programs	permanent backup
Latched area	permanent backup

■ Lithium button battery for Real Time Clock (RTC) function




	PLC power off
RTC	keeps accurate time

Accurate Axis Control - Positioning Control Solution



■ Positioning control - Delta's CANopen Control


- Delivers up to 8-axis CANopen positioning control with AS-FCOPM communication card
- Fast positioning configuration in one initialization instruction without building CANopen data exchange table
- Batch download programmable servo drive parameters avoids risk of loss
- Axis control by instructions provides easy maintenance and high PLC program readability



■ Simple control instructions for AC Servo Drive ASDA-A2 Series

- Initialization: INITC
- Relative positioning: DRVIC
- Read and write parameter: COPRW
- Acceleration and deceleration: CASD
- Constant speed control: PLSVC
- Absolute positioning: DRVAC
- Start/Stop: ASDON
- Homing: ZRNC

ASDA-A2 back and forth motion control in 4 steps



Pulse 




Motion control of max. 6
Delta AC Servo Drives ASDA-B2 Series

■ Positioning control - high-speed pulse

- AS332T-A/AS332P-A transistor CPU: 6 axes (or 12 channels) 200 kHz
- AS324MT-A differential CPU: 2 axes 4 MHz + 4 axes 200 kHz
- Supports positioning planning table for fast positioning planning and path simulation
- Choose any given 2 axes for linear and arc interpolation

* Note: Please refer to the product specification section (P.23) for more information on CPU models





AC Servo Drive
ASDA-B2 Series

■ High-speed counter

- Real-time high precision monitoring:
AS332T-A/AS332P-A transistor CPU: 6 channels 200 kHz
AS324MT-A differential CPU: 2 channels 4 MHz/4 channels 200 kHz
- Up to 16 external input interrupts
- High-speed counter setting tools



* Note: Please refer to the product specification section (P.23) for more information on CPU models



Simple Installation

■ Easy installation design

- Space-saving design suitable for installation in control panels



■ Rackless Din-rail installation

- Delta patented design

▶ Robust slot and clip interlocking design



■ Fast disassembly

- Release the clip ring to easily take out the module from the front without moving adjacent modules




■ Simple installation process

- Press the clip rings and push the module to the desired position until hearing a "click" to finish installation



■ Convenient grounding protection

- Install on Din-rail: CPU module and expansion modules can be installed directly on Din-rail without backplane
- Install with screw: pull out the installation clip ring and directly install it on the panel
- Both methods are equipped with ground protection



■ Screwless and time-saving installation




- Time-saving installation
Complete I/O wiring in 1 second




■ Robust Loose-proof spring clamp terminal block

- In commonly used spring clamp terminal blocks, the clamping force is determined by the spring material, which decreases with the aging of the spring.



The green arrow is the clamping force, and the red arrow is the pull-out force.

- The AS Series adopts the full-covered spring clamp design that enhances the clamping force. When the wire is pulled-out (red arrow) and the spring moves up (green arrow), a downward force is generated (blue arrow) to clamp the wire.




Industrial Network Solution

EtherNet/IP Solution

The open industrial Ethernet communication protocol for real-time control and data collection


EtherNet/IP[®]

- Max. connectable slave stations: 32
- Max. data transmission: 500 bytes/connection
- Performance: slave station data update in 1 scan time




Flexible network system configuration


- Supports star, linear network topology for fast expansion and management on production lines
- Compatible with IT network. No independent network or IT technician required
- Combines with Delta IES solution to construct IoT for more automation applications and industrial 4.0 upgrades



One cable, one network

- Complete Delta EtherNet/IP solution connects different equipment via Ethernet cable and simplify cable preparation
- Replaces traditional 3-layer industrial network structure with seamless connection via 100 MB high-speed network
- Complete industrial network diagnosis for shortened debug time






IoT & Industrial Ethernet

- DIACloud platform connection
- Redundancy ring recovery time < 20 ms
- Industrial class EMC testing


■ Software integration

- Consistent data exchange interfaceshortens learning time with fast system configuration
- Provides Delta equipment parameterlist for quick parameter matching without looking into detailed manual
- EDS File provides quick connection with EtherNet/IP products of other brands




■ Accurate data update

- Provides real-time cyclic and acyclic data transmission and define data priority between equipment
- Establishes multiple CIP links and define different register priority with one piece of equipment
- Executes data update based on user RPI. Updates all slave station data in one scan time
- 70% better stability compared with traditional Modbus TCP




EtherNet/IP Software EIP Builder




- **Visualized Network Mapping**

- Direct network planning



■ Network Mapping Diagnosis

- Real-time network status and device indicators display



Parameter List

- Built-in parameter list of Delta's products

AS Parameters	Set to Default	Name	Value	Unit
P000		No.		
P005		No.		
P010		No.		
P015	1000	R	[0000] P010-R Identity Code	0
P020	1000	R	[0000] P010-R Rated Current	0
P040	1002	N/W	[0002] P040-Parameter Bld	0
P045	1002	N/W	[0002] P045-Parameter Bld	0
P050	1002	N/W	[0002] P050-Start up Delay	0
P055	1004	N/W	[0004] P055-Start up Delay	0
P065	1005	N/W	[0005] P065-IP page size	0.00
P070	1006	N	[0006] P070-Parameter version	0.00
P075	1007	N	[0007] P075-Parameter Decoder	0.00
P100	1008	N/W	[0008] P100-Parameter Decoder	0.00
P105				
P120				
P125				
Default No. Min: 0000.00 Max: 0.00 Help String				

■ Data Exchange Table

- Data exchange via table blanks filling. PLC programming is not required

P2P Network Setup

Options: [OK] [Cancel] [Home] [Advanced] [Data Exchange Setup] [GUI] [Data Exchange Group] [Home]

Mode: [Program Control]

Data Exchange Group

Name	Seed	Remote Status Address	Local Address	Remote Address	Quantity
1	1	192.168.1.1	192.168.1.1	192.168.1.1	1
2	1	192.168.1.1	192.168.1.1	192.168.1.1	1
3	1	192.168.1.1	192.168.1.1	192.168.1.1	1

Buttons: [Add] [Delete] [Copy]

Bottom: [OK] [Cancel]

- Data Input/Output Corresponding Table

- Preset data exchange on corresponding parameters
- Connecting equipment editing on corresponding parameters

Parameter Setting

IO Connection

No.	OUT	Name	Value
1	X	D1802 Output	0
2	X	D1802 Status	0
3	X	D1802 Pres. Command	0
4	X	D1802 Pres. Output	0
5	X	D1802 Output Current	0
6	X	D1802 DC Out Voltage	0
7	X	D1802 Output Voltage	0
8	X	D1807 Multi-Speed	0
9	X	D1808 Resonance	0
10	X	D1809 Clutch	0
11	X	D1802 Output Index	0
12	X	D1802 Output	0
13	X	D1802 Control Speed	0
14	X	D1802 PG pulse	0
15	X	D1802 PG pulse	0
16	X	D1802 Output power	0
17	X	D1802 Status	0
18	X	D1802 Current mode	0
19	X	D1802 Control Speed	0
20	X	D1802 Resonance	0
21	X	D1802 Current Phs. L	0
22	X	D1802 Current Phs. L	0

OK Cancel


■ Data Exchange Diagnosis

- Data exchange status and error codes

Connection Properties - 3										
	Widget	Enable	IP Address	Adapter Name	CPU Address	Adapter Address/Port/Name	Length (bits)	Property	Error Description	
1	100	☒	192.168.1.201	Shw_1	00	10 00	200			
2	100	☒	192.168.1.212	Shw_2	0100	10 00	200			
3	100	☒	192.168.1.212	Shw_2	0100	10 00	200			
4	100	☒	192.168.1.20	Shw_3	00	01000 00	200		The connection timeout.	

Visualized Product List

- Visualized equipment selection




IP Management Function

- Configure all IP address of all EtherNet/IP products

The screenshot shows the 'IP Manager' application. The main window is titled 'IP Manager' and has a menu bar with 'File', 'Edit', 'View', 'Tools', and 'Help'. Below the menu bar is a toolbar with various icons. The main window is divided into two panes. The left pane is titled 'Table of Existing Devices' and contains a table with columns: 'IP', 'Type', 'MAC Address', and 'Name'. The table has one row: '192.168.1.1' | '192.168.1.1' | '192.168.1.1' | '192.168.1.1'. The right pane is titled 'Network Interface' and contains a table with columns: 'Name', 'Type', 'MAC Address', and 'Name'. The table has one row: '192.168.1.1' | '192.168.1.1' | '192.168.1.1' | '192.168.1.1'.



Equipment Description	Management Function
1. Equipment	
2. Description	
3. Management Function	



Remote I/O Solution


CANopen Remote I/O

- Max quantity of RIO stations: 15 stations
- Max quantity of IO modules (CPU right side + RIO (SCM) right side): 32 modules
 - Max DIO points: 1,024 points
 - Max quantity of AIO modules: 16 modules
 - Max quantity of communication modules: 4 modules (Only installed on CPU right side)
 - Max quantity of IO modules installed on RIO (SCM) right side: 8 modules
- AS-FCOPM can only be installed in slot 2 of the CPU and SCM
 - When a CPU is installed as AS-FCOPM in slot 2, then slot 1 can be used to install another function card except AS-FCOPM
 - When SCM is working in RIO (RTU) mode, then slot 1 is disabled




■ Hardware Configuration

- Hardware parameter complete planning



Visualized I/O Structure

- Direct I/O planning



■ I/O Product List

- Product description and specification




I/O Without Planning ■

- Auto-mapping with I/O addresses in CPU (X,Y, and D)

DIO		Type	Name	Input Device Range	Output Device Range	Comment
	Power Module					
	Reverse Module	Network Module	AS5050A	C2000 - C2003	C2001 - C2003	
	Function Card					
	Function Card	Function Card	AS4FC01			
	Module Information	Digital IO Module	AS5050M01	Y1-0 - Y1-15		
	Module Information	Digital IO Module	AS5060M01		Y1-0 - Y1-15	
	Module Information	Digital IO Module	AS1640M01	Y2-0 - Y2-15		
	Module Information	Digital IO Module	AS1640M11		Y2-0 - Y2-15	
	Module Information	Digital IO Module	AS1640M11	Y3-0 - Y3-15		
	Module Information	Digital IO Module	AS1640M01		Y3-0 - Y3-15	
	Module Information	Digital IO Module	AS1640M01	Y4-0 - Y4-15		


AIO		Type	Name	Input Device Range	Output Device Range	Comment
Power Mode	Internal Module	AIO500A	A	02916 ~ 02918	02916 ~ 02919	
Function Code						
Function Code	Function Code	AIO400M	A	02920 ~ 02929		
Module Information / Analog I/O Module	AIO400A	A	02920 ~ 02929	02920 ~ 02929	D16: 016~024, 024: 016~024, 024: 024, 024: 024	
Module Information / Analog I/O Module	AIO400A	A	02930 ~ 02939	02930 ~ 02939	D16: 016~024, 024: 016~024, 024: 024, 024: 024	
Module Information / Analog I/O Module	AIO400A	A	02940 ~ 02949	02940 ~ 02949	D16: 016~024, 024: 016~024, 024: 024, 024: 024	
Module Information / Analog I/O Module	AIO400A	A	02950 ~ 02959	02950 ~ 02959	D16: 016~024, 024: 016~024, 024: 024, 024: 024	
Module Information / Analog I/O Module	AIO500A	A	02960 ~ 02969	02960 ~ 02969	D16: 016~024, 024: 016~024, 024: 024, 024: 024	
Module Information / Analog I/O Module	AIO500A	A	02970 ~ 02979	02970 ~ 02979	D16: 016~024, 024: 016~024, 024: 024, 024: 024	

Serial Communication Solution




■ Modbus Mode

- Easy data exchange configuration



■ Real-time history log diagnosis

- AS00SCM stores 2k bytes history log. SCMSoft directly displays the log for real-time communication status monitoring with no additional monitoring software required




■ UD Link Mode (User-defined)

- Easy connection to end equipment of special communication protocols


Traditional programming structure

Instruction receiving, accessing, editing, transmitting, sequence control



Connection to end equipment of special communication protocols

- Editing the transmitting/receiving packets via SCMSoft. Format exchange and checksum calculation via AS00SCM
- Packet content auto-combination for logic control in PLC, reducing PLC program complexity
- Max. 1,000 transmitting/receiving packets



Instruction execution sequence planning


* Command No.	Command Type	Send Packet	Recv Packet	Success	Fail	Retry	Repeat	Send Wait
1	Send & Receive	TX Packet1	RX Packet1	Goto : 1	Goto : 1	0	2	0
2	Send & Receive	TX Packet2	RX Packet2	Goto : 2	Goto : 1	0	3	0
3	Send & Receive	TX Packet21	RX Packet3	Goto : 3	Goto : 1	0	4	0
4	Send & Receive	TX Packet25	RX Packet4	Goto : 4	Goto : 1	0	5	0
5	Send & Receive	TX Packet28	RX Packet5	Goto : 5	Goto : 1	0	6	0

User-defined communication format editing

Programming and Diagnosis Functions


ISPSoft IEC Programming Software

Easy operation greatly enhances efficiency



Data Tracer/Logger

- Data log and time-sequential analysis




Positioning Planning Tool

- Table-structured position planning

The screenshot shows the Positioning Planning Tool interface, which includes a table for position planning. The table has columns for 'No.', 'Axis', 'Position', 'Speed', 'Acceleration', 'Deceleration', 'Completion', and 'Status'. The table is populated with data for various positions and their associated parameters.


CARD Utility

- Data backup tool




COMMGR

- Communication interface manager




HWCONFIG

- Hardware configuration and parameter setting




EIP Builder

- EtherNet/IP network configuration



CANopen Builder


- CANopen network configuration



Modular Program Structure


Traditional program structure

Errors are often found in large-scale programs under a traditional structure. It's hard to debug with increased maintenance cost.




Modular program structure

Programming organization unit (POU) enables easy management in large-scale programs with high development efficiency.



Modular Program Structure



Task manager

Plan the execution sequence of POU's and define the nature of the tasks (cyclical or interruptive)

POU management

Manage all POU's via project tree and support POU import/export for joint development or other uses


User library

Built-in variety of Delta developed FBs. Users can add frequently used FBs to the library for future use.

Convenient Programming

- **User-defined data type**

In addition to basic data types, users can define structures and enumerations for flexible programming




- **On-line programming/update**

Supports program editing in monitoring mode and program updates during equipment operation for convenient debugging and maintenance



- **Debugging mode**

Supports breakpoints, single step execution and other functions to enhance debugging efficiency



Various Programming Languages

- **Support multiple programming languages in the same project**

- **Ladder Diagram (LD)**

ISPSOft provides a programming interface with the widely used LD language for faster programming



- **Structured Text (ST)**

Similar programming method to advanced programming language C or PASCAL. ST provides more convenient editing for complicated expression

```

// Calculate the total rate
// If (Rate and (Not Err)) THEN
//   TotalRate := TotalRate + 1;
// END_IF;
// END_IF;
// END_IF;
// END_IF;
// END_IF;
// END_IF;

```

- **Continuous Function Chart (CFC)**


CFC provides more advanced applications than FBD. It supports data feedback, direct display of data stream and execution sequence for motion control and sequence-centered application



Note: ISPSOft V3.01 supports CFC language


- **Sequential Function Chart (SFC)**

Direct and easy expression for the steps in flow charts for applications that require process control



Easy Hardware Configuration and Parameter Setting

HWCONFIG




- **Graphic panel for module configuration**
Easy configuration based on connecting equipment scanning for quick setup

- **I/O listing**
Direct display for corresponding device addresses after configuration




Note: Fill the table to configure module parameters quickly.
From/To instruction is not required for module initialization.

- **Parameter setting**
Fast parameter setting on controller and modules without manual reference or programming




- **Module configuration method**



- **Smart module configuration**


Supports an advanced planning tool for a variety of network modules



Complete Diagnosis Tools for Quick and Effective System Monitoring


Data Logger/Tracer

- Real-time
- Stable
- Precise



- **Real-time monitoring:**
High-speed tracer for fast sampling within 1 scanning cycle
- **Stable logging:**
Long-time data logger savings of up to 32,768 data records, which can be transferred to SD card
- **Precise data capture:**
Supports a variety of sampling intervals and trigger modes
- **Convenient comparison:**
Multiple data logs in various data formats can be recorded at the same time
- **Efficient data analysis:**
Supports trend display, scaling, arrangement, merge and measurement

Real-time Module Monitoring




- **Visualized monitoring**
Direct monitoring interface provides real-time status on modules via LED indicators
- **Module comparison**
Real-time inspection of actual module settings to ensure consistency
- **Error logs**
Immediate inquiry for error messages and logs of abnormal modules
- **Module information**
Provides model name and version of current modules



Convenient Software Wizards for Effortless Planning

Position planning table



2D simulation

Intuitive 2D track simulation without complicated calculation for real-time path planning

Path list

Multiple combinations for positioning modes and tracks
Fast path planning via table-structured planning

Axis parameter setting

Intuitive configuration interface for easy axis parameter setting without manual reference

High-speed counter setting tool


Counter index will display corresponding contact point, device and counter specification once the counting mode is chosen. Fast planning without manual reference for enhanced development efficiency.

One-time setting

The dialog box shows settings for a high-speed counter. It includes fields for Type, Input Port, Counter, and Arrival Value. There are also checkboxes for 24VDC input, Maximum input frequency, Set Up Down counter mode, Increment/Decrement input point, Enable/disable the reset input function, Reset input point, and Set the counting mode.

Data backup tool - CARD Utility

Friendly guidance interface for easy data backup and restore on programs, parameters and devices



Various backup and restore methods for flexible management and operation



Data backup to PC




Data backup to SD card

Multiple Security Protection for Programs and Data

■ Security: provides 6 types of program protection for data safety

- 16-digit password protection on main program
- 16-digit password protection on FBs
- Access denial mechanism on error login
- Data upload protection function
- Verification between Project (Programming ID) and CPU (PLC ID)



- Prevention of direct copy from IC



Model Name Explanation

CPU Module

AS332T-A

AS	3	32	T	-	A
Series	Model	IO Pts.	Output type		Type
	3: 300 2: 200	00: None 18: 18 Pts. 20: 20 Pts. 24: 24 Pts. 28: 28 Pts. 32: 32 Pts.	N: None T: NPN P: PNP R: Relay MT: NPN+Diff.		【300 CPU】 A: HDC terminal B: EU terminal 【200 CPU】 A: Basic

Digital I/O Module

AS08AM10N-A

AS	08	AM	1	0	N	-	A
Series	IO Pts.	Classification	Function	Output type	Type		
	08: 8 Pts. 16: 16 Pts. 32: 32 Pts. 64: 64 Pts.	AM: Digital input AN: Digital output AP: Digital input/output	0: No input 1: DC input (24V)	0: No output 1: 0.5A transistor/2A relay output 2: 0.1A transistor output	N: No output T: NPN P: PNP R: Relay		A: Basic

Analog I/O Module

AS04AD-A

AS	04	AD	-	A
Series	IO Channels	Classification	Type	
	04: 4-channel 06: 6-channel 08: 8-channel	AD: Analog input DA: Analog output XA: Analog input/output	A: Voltage/Current B: Voltage C: Current	

Motion Module

AS02PU-A

AS	02	PU	-	A
Series	IO Channels	Classification	Type	
	02: 2-channel 04: 4-channel	PU: Pulse-train output	A: Basic	

Temperature & Load Cell Module

AS04RTD-A

AS	04	RTD	-	A
Series	IO Channels	Classification	Type	
	02: 2-channel 04: 4-channel 06: 6-channel 08: 8-channel	RTD: Platinum resistance thermometer TC: Thermocouple LC: Load cell	A: Basic	

Communication Module

AS00SCM-A

AS	00	SCM	-	A
Series	Function	Classification	Function	
	00: Basement 01: Basic	SCM: Serial DENT: DeviceNet	A: Basic	

Function Card

AS-F232


AS	-	F	232
Series	Classification	Function	
	F: Function card	232: RS-232 422: RS-422 485: RS-485 COPM: CANopen 2AD: 2-channel analog input 2DA: 2-channel analog output EN02: Ethernet PFN02: PROFINET	

Power Supply Module

AS-PS02

AS	-	PS	02
Series	Classification	Function	
	PS: Power supply	02: AC Input (100~240V) 02A: AC Input (100~240V) + DC Output (24V, 0.5A)	

Product Models and Specifications



CPU Module

AS300 CPU



AS300 Series CPU standard specification				
Program capacity 128k steps	Basic instruction 25ns	I/O capability: 1,024 Expansion modules: 32		
USB/RS-485 x 2/EtherNet	Micro SD Card	Function card x 2	EtherNet/IP Modbus CANopen remote I/O ^(*)	CANopen DS301 Position Control ^(*)
Model	Built-in I/O	High speed output	High speed input	
AS332T-A AS332P-A	16DI/16DO	6 axes 200kHz pulse output	6 channels 200 kHz high-speed counters	
AS324MT-A (Differential)	12DI/12DO	2 axes + 4 axes 200 kHz pulse output	2 channels + 4 channels 200 kHz high-speed counters	
AS320T-B AS320P-B	8DI/12DO	6 axes 200 kHz pulse output	4 channels 200 kHz high-speed counters	
AS300N-A	-	-	-	

*1: Needs CANopen function card

AS200 CPU



AS200 Series CPU standard specification			
Program capacity 64k steps	Basic instruction 25ns	I/O capability: 1,024 Expansion modules: 32	
USB/RS-485 x 2/EtherNet/CANopen	Micro SD Card	EtherNet/IP, Modbus CANopen remote I/O	CANopen DS301 Position Control
Model	Built-in I/O	High speed output	High speed input
AS228T-A AS228P-A AS228R-A	16DI/12DO	6 axes 200 kHz pulse output	4 channels 200 kHz high-speed counters
AS218TX-A AS218PX-A AS218RX-A	8DI/6DO 2AI/2AO	3 axes 200 kHz pulse output	4 channels 200 kHz high-speed counters

Power Supply AS-PS02		Power Supply AS-PS02A	
	Input 100V _{AC} ~ 240V _{AC}		Input 100V _{AC} ~ 240V _{AC}
	24V _{DC} , 2A (for internal bus)		24V _{DC} , 1.5A (for internal bus) 24V _{DC} , 0.5A (for external I/O)

Product Specifications

Model		AS332T-A AS332P-A	AS324MT-A	AS320T-B AS320P-B	AS300N-A	AS228T-A AS228P-A AS228R-A	AS218TX-A AS218PX-A AS218RX-A
Programming Languages		Ladder Diagram (LD), Structured Text (ST), Continuous Function Chart (CFC), Sequential Function Chart (SFC)					
Instruction Processing Speed	LD Instruction	25 ns					
	MOV Instruction	0.15 μs					
	Elementary Arithmetic for Integer	0.92 μs ~ 1.02 μs					
	Elementary Arithmetic for Floating Point	1.69 ~ 1.85 μs					
Program Capacity		128k steps				64k steps	
Memory Capacity	Data (D)	64k words (including 30k user-defined, 30k software configuration and 4k special registers)					
	Extension (FR)	64k words (user parameter storage)					
Function Card		The CPUs support up to 2 function cards				-	
Max. Extension Modules		32 modules (max. 16 analog modules/4 communication modules)					
Max. Number of Inputs/Outputs		1,024 points (input & output)					
CPU Built-in Inputs/Outputs		16DI/16DO	12DI/12DO	8DI/12DO	-	16DI/12DO	8DI/6DO, 2AI/2AO
CPU Built-in Differential Inputs/Outputs		-	4 Inputs + 4 Outputs	-			
Inputs/Outputs	X	1,024 inputs (X0.0 ~ X63.15)					
	Y	1,024 outputs (Y0.0 ~ Y63.15)					
Bit Devices	M	8,192 bits (M0 ~ M8191)					
	S	2,048 bits (S0 ~ S2047)					
Timer	T	512 (T0 ~ T511)					
16-bit Counter	C	512 (C0 ~ C511)					
32-bit Counter	HC	256 (HC0 ~ HC255)					
Pulse Output		Open collector: 6 axes, 200 kHz	Open collector: 4 axes, 200 kHz Differential: 2 axes, 4 MHz	Open collector: 6 axes, 200 kHz	-	Open collector: 6 axes, 200 kHz	Open collector: 3 axes, 200 kHz
High-Speed Counter		General: 6 CHs, 200 kHz	General: 4 CHs, 200 kHz Differential: 2 CHs, 4 MHz	General: 4 CHs, 200 kHz	-	General: 4 CHs, 200 kHz	General: 4 CHs, 200 kHz
DO Type		AS332T-A: NPN AS332P-A: PNP	Diff./NPN	AS320T-B: NPN AS320P-B: PNP	-	AS228T-A: NPN AS228P-A: PNP AS228R-A: Relay	AS218TX-A: NPN AS218PX-A: PNP AS218RX-A: Relay
Built-in Communication Port		USB, Ethernet, RS-485 x2				USB, Ethernet, RS-485 x2, CANopen	
Communication Protocol		Modbus, Modbus TCP, EtherNet/IP, CANopen (requires a CANopen function card)				Modbus, Modbus TCP, EtherNet/IP, CANopen	
Ethernet Connection Resource		Modbus (Client/Server): 32/32 EtherNet/IP (CIP): 32				Modbus (Client/Server): 16/16 EtherNet/IP (CIP): 16	

Product Specifications

Model		AS332T-A AS332P-A	AS324MT-A	AS320T-B AS320P-B	AS300N-A	AS228T-A AS228P-A AS228R-A	AS218TX-A AS218PX-A AS218RX-A
Data Backup (Without Battery)	Program	Flash ROM, rewritable up to 100,000 times					
	Latched Area	MRAM, no rewriting limit					
CANopen DS301	Connectable Slave Stations	Max. 64 points					
	PDO Data Capacity (Host)	Max. 2,000 bytes (Read & Write)					
	PDO Data Capacity (Slave)	Max. 8 PDO (Read & Write); Max. 8 bytes for each PDO					
Real-time Clock (RTC)		General Lithium button battery (CR1620)					
Self-Diagnosis Function		diagnoses CPU errors, built-in memory errors, and more					
Rated Input Current	AS-PS02/AS-PS02A	110 V _{AC} ~ 240 V _{AC} (±10%)					
	CPU	24 V _{DC} (±10%)					
	Extension modules						

Electrical and Environmental Specifications

Item		Specifications
Internal Power Consumption	CPU	150 mA
	Extension Module	Digital relay output <150 mA, Other modules < 80 mA
Operating Temperature		-20 ~ 60 °C
Storage Temperature		-40 ~ 80 °C
Operating Humidity		5 ~ 95%, non-condensing
Storage Humidity		5 ~ 95%, non-condensing
Vibration		IEC 61131-2, IEC 60068-2-6 (TEST Fc); 5 Hz ≤ f ≤ 8.4 Hz, constant amplitude 3.5 mm; 8.4 Hz ≤ f ≤ 150 Hz, constant acceleration 1g
Shock		IEC 61131-2, IEC 60068-2-27 (TEST Ea); 15g peak, 11 ms duration, half-sine
Operating Environment		Non-corrosive gas
Installation		Inside of the control panel
Pollution Degree		2
Protection Rating		IP20

Ethernet Specifications

Item			AS300 Series	AS200 Series	Note
Protocol			Modbus TCP, EtherNet/IP, SMTP, HTTP		Supports all protocols at the same time
Modbus TCP	Connection (Server)		32	16	
	Connection (Client)		32	16	
	RTU-EN01 Connection		4	4	
Socket	TCP Connection		4	2	
	UDP Connection		4	2	
SMTP	E-mail Connection		4	2	
EtherNet/IP	Operation Mode		Scanner /Adapter		
	CIP_IO Connection	CIP Connection	32 (Client+Server)	16 (Client+Server)	Shared with IO Connection
		TCP Connection	16 (Client+Server)	8 (Client+Server)	Shared with IO Connection
		Requested Packet Interval (RPI)	5 ms ~ 1,000 ms		Default: 20 ms
		Max. Performance	3,000pps		
		Max. Capacity per Connection	500bytes		
	CIP_Explicit Message	Class 3 (Connected Type)	32 (Servers), shared with UCMM	16 (Servers), shared with UCMM	Shared with IO Connection
		UCMM (Non-Connected Type)	32 (Clients + Servers), shared with Class 3	16 (Clients + Servers), shared with Class 3	Shared with IO Connection
		Supported CIP Objects	Identity, Message Router, Assembly, Connection Manager, Port, TCP/IP interface, Ethernet link, Vendor specific		
	CIP_Produced TAG	Max. CIP Connections	32 (Servers)	16 (Servers)	Shared with IO Connection
		Max. Capacity	400 bytes		
		Requested Packet Interval (RPI)	5 ms ~ 1000ms		
	CIP_Consumed TAG	Max. CIP Connections	32 (Clients + Servers)	16 (Clients + Servers)	Shared with IO Connection
		Max. capacity	400 bytes		
		Requested Packet Interval (RPI)	5 ms ~ 1000ms		
	AS00SCM (RTU) + AS-FEN02 Connection Nodes		15	8	AS RTU Mode

Please visit Delta's official website for selection

AS Series I/O Modules

■ Digital I/O Modules (Input)

				Rated input voltage 5 ~ 24 V _{DC}
				Response time 1 ms
				Filter function 1 ~ 20 ms
				Screwless removable terminal block 8 / 16 inputs
8 inputs	16 inputs	32 inputs	64 inputs	
Faster wiring terminal block	Faster wiring terminal block	High-density MIL terminal block	High-density MIL terminal block	
AS08AM10N-A	AS16AM10N-A	AS32AM10N-A	AS64AM10N-A	

■ Digital I/O Modules (Output)

				NPN (Sink) or PNP (Source) module
				Response time 1 ms (Transistor) 10 ms (Relay)
				Screwless removable terminal block 8 / 16 outputs
8 outputs	8 outputs	8 outputs	32 outputs	
Faster wiring terminal block Transistor output NPN (Sink)	Faster wiring terminal block Relay output	Faster wiring terminal block Transistor output PNP (Source)	High-density MIL terminal block Transistor output NPN (Sink)	
AS08AN01T-A	AS08AN01R-A	AS08AN01P-A	AS32AN02T-A	

				
16 outputs	16 outputs	16 outputs	64 outputs	
Faster wiring terminal block Transistor output NPN (Sink)	Faster wiring terminal block Relay output	Faster wiring terminal block Transistor output PNP (Source)	High-density MIL terminal block Transistor output NPN (Sink)	
AS16AN01T-A	AS16AN01R-A	AS16AN01P-A	AS64AN02T-A	

■ Digital I/O Modules (Mixed)



16 inputs / outputs

Faster wiring terminal block
8 inputs/8 transistor outputs
NPN (Sink)

AS16AP11T-A

16 inputs / outputs

Faster wiring terminal block
8 inputs
8 relay outputs

AS16AP11R-A

16 inputs / outputs

Faster wiring terminal block
8 inputs/8 transistor outputs
PNP (Source)

AS16AP11P-A

NPN (Sink)
or PNP (Source) module

Rated input voltage
5~24 V_{DC}

Filter function
1~20 ms

Screwless removable terminal block

Response time
1 ms (Transistor)
10 ms (Relay)

■ Analog I/O Modules



4 channels

Analog input

AS04AD-A

8 channels

Analog input

AS08AD-B **New**

8 channels

Analog input

AS08AD-C **New**

4 channels

Analog output

AS04DA-A

6 channels

Analog input/output

AS06XA-A

Conversion time
2 ms/channel

50/60 Hz filter

A: Voltage and current
B: Voltage
C: Current

Resolution
AI: 16-bit
AO: 12-bit

Accuracy ±0.2%

4/6/8 CH

Module
monitoring/configuration

Differential inputs

■ Load Cell Module



2 channels

AS02LC-A

Functions

50/60 Hz filter

High-speed
dynamic
measurement

2 channels of
independent
sampling

Accuracy 0.4%
full range

2 CH

Connectable to
4-wire/6-wire
load cell sensor

full range

Filter function

Multiple-point
calibration

Online
monitoring/
configuration

■ Pulse Unit Modules



2 channels

Differential

AS02PU-A **New**



4 channels

Open Collector

AS04PU-A **New**

Input: 200 kHz

Output: 200 kHz

Open Collector/Diff.

2/4 CH

Support Motion APIs

AS Series I/O Modules

■ Temperature Measurement Modules

		Conversion time 200 ms/channel		Resolution 0.1°C/0.1°F	Wire breaking detection
4 channels	6 channels	Overall accuracy ±0.1%	50/60 Hz filter	Module monitoring/configuration	4/6 CH
PT, NI temperature sensor	PT, NI temperature sensor	Pt100/Ni100/Pt1000/Ni1000/JPt100/LG-Ni1000/Cu50/Cu100, resistor 0~300Ω, 0~3,000Ω			
AS04RTD-A	AS06RTD-A New				
		Conversion time 200 ms/channel		Resolution 0.1°C/0.1°F	Disconnection detection
4 channels	8 channels	Overall accuracy ±0.5%	50/60 Hz filter	Module monitoring/configuration	4/8 CH
TC temperature sensor	TC temperature sensor	J, K, R, S, T, E, N, B type thermocouple; ±100 mV			
AS04TC-A	AS08TC-A New				

■ Communication Modules

2 COM ports

AS00SCM-A

COM port

RS-232C

RS-422

RS-485

CANopen

Function

Selectable COM ports; supporting standard Modbus protocol and user-defined protocol

Delta communication protocol

Software

SCMSOft

Data exchange table for quick setup

Real-time monitoring on communication status

DeviceNet

AS01DNET-A **New**

COM port

DeviceNet


Function


DeviceNet protocol (master/slave) and support RTU mode


Software

DeviceNet Builder




Accessory Selection for High-density Modules




Model Name		
AS332T-A AS332P-A AS324MT-A	UC-ET010-24D (1M) UC-ET020-24D (2M) UC-ET030-24D (3M)	UB-10-ID16A
		
		
		

Model Name				
UB-10-ID16A	UC-ET010-24D (1M) UC-ET020-24D (2M) UC-ET030-24D (3M)	AS32AM10N-A	UC-ET010-24B (1M) UC-ET020-24B (2M) UC-ET030-24B (3M)	UB-10-ID32A
				

Model Name					
UB-10-ID16A or UB-10-OR16A (Relay)	UC-ET010-24D (1M) UC-ET020-24D (2M) UC-ET030-24D (3M)	AS32AN02T-A	UC-ET010-24B (1M) UC-ET020-24B (2M) UC-ET030-24B (3M)	UB-10-OT32A	
					

Accessory Selection for High-density Modules

Model Name				
UB-10-ID16A	UC-ET010-24D (1M) UC-ET020-24D (2M) UC-ET030-24D (3M)	AS64AM10N-A	UC-ET010-24B (1M) UC-ET020-24B (2M) UC-ET030-24B (3M)	UB-10-ID32A
				


Model Name				
UB-10-ID16A or UB-10-OR16A (Relay)	UC-ET010-24D (1M) UC-ET020-24D (2M) UC-ET030-24D (3M)	AS64AN02T-A	UC-ET010-24B (1M) UC-ET020-24B (2M) UC-ET030-24B (3M)	UB-10-OT32A
				

Dimensions


CPU Modules

Dimensions are in mm


AS332T-A, AS332P-A, AS324MT-A




AS300N-A **New**



AS320T-B **New**, AS320P-B **New**




AS228T-A **New**, AS228P-A **New**, AS228R-A **New**
AS218TX-A **New**, AS218PX-A **New**, AS218RX-A **New**




Digital I/O Modules

Dimensions are in mm


AS08AM10N-A, AS08AN01R-A,
AS08AN01T-A, AS08AN01P-A




AS16AM10N-A, AS16AN01R-A, AS16AN01T-A,
AS16AN01P-A, AS16AP11R-A, AS16AP11T-A,
AS16AP11P-A



AS32AM10N-A, AS32AN02T-A



AS64AM10N-A, AS64AN02T-A




Dimensions

Power Supply Modules

Dimensions are in mm


AS-PS02, AS-PS02A



Pulse Unit Module

Dimensions are in mm


AS02PU-A **New**, AS04PU-A **New**




Communication Modules

Dimensions are in mm

AS00SCM-A




AS01DNET-A **New**



Analog Modules

Dimensions are in mm


AS02LC-A, AS04AD-A, AS04DA-A, S04TC-A,
AS04RTD-A, AS06XA-A, AS08AD-B **New**, AS08AD-C **New**,
AS06RTD-A **New**, AS08TC-A **New**



Connector Converter

Dimensions are in mm


UB-10-IO32D **New**




Function Cards

Dimensions are in mm


AS-F232




AS-FCOPM



AS-F2AD, AS-F2DA,
AS-F422, AS-F485





AS-FEN02 **New**
AS-PPFN02 **New**



Installation Notes


Dimensions are in mm




Cable (MIL)

Dimensions are in mm

UC-ET010-24D (1 M), UC-ET020-24D (2 M),
UC-ET030-24D (3 M)



UC-ET010-24B (1 M), UC-ET020-24B (2 M),
UC-ET030-24B (3 M)



Serial	Name	Description
①	40-pin terminal	Connect to modules
②	20-pin terminal	Connect to external terminal modules UB-10-ID16A or UB-10-OR16A or UB-10-OR16B


Serial	Name	Description
①	40-pin terminal	Connect to modules
②	40-pin terminal	Connect to external terminal modules UB-10-ID32A or UB-10-OT32A

Dimensions


External Terminal Modules

Dimensions are in mm


UB-10-OR16A, UB-10-OR16B




UB-10-OT32A



UB-10-ID16A




UB-10-ID32A



Auxiliary Connected Power Module

Dimensions are in mm

AS-ATXB



Ordering Information

■ CPU Module

Name	Model	Instruction Speed/Performance	Memory / CPU Clock	Max. Inputs & Outputs/Extension Module (Max. Extension Racks)	Memory Card	Certification
CPU	All models	LD: 25 ns MOV: 0.15 μs 40k steps/1ms (LD 40%, MOV 60%)	RAM: 2 MB ROM: 4 MB CPU clock: 400 MHz	1,024 inputs & outputs/32 modules (Max. 15 extension racks)	Micro SD Max. 32GB	CE/UL

Name	Model	Program Capacity	Built-in I/O	DO Type	Terminal Block	High-Speed Counter	Pulse-train Output	Built-in Communication	Function Card Slot
CPU	AS332T-A	128k steps	16DI/16DO	NPN	MIL	6 CHs, 200 kHz	6 Axes, 200 kHz (12 CHs, 200 kHz)	USB RS-485*2 Ethernet	2
	AS332P-A			PNP					
	AS324MT-A		12DI/12DO	Diff./NPN		EU	2 CHs, 4 MHz (Diff.) 4 CHs, 200 kHz		
	AS320T-B New			NPN					
	AS320P-B New		8DI/12DO	PNP	4 CHs, 200 kHz		6 Axes, 200 kHz (12 CHs, 200 kHz)		
	AS300N-A New			-		-			
	AS228T-A New	64k steps	16DI/12DO	NPN	EU	4 CHs, 200 kHz	6 Axes, 200 kHz (12 CHs, 200 kHz)	USB RS-485*2 Ethernet CANopen	-
	AS228P-A New			PNP					
	AS228R-A New			Relay			-		
	AS218TX-A New		8DI/6DO 2AI/2AO ⁽¹⁾	NPN		4 CHs, 200 kHz	3 Axes, 200 kHz (6 CHs, 200 kHz)		
	AS218PX-A New			PNP					
	AS218RX-A New			Relay			-		

Note: The specifications of the built-in AIO are the same as AS-F2AD/AS-F2DA function cards.

■ Software

Product Name	License	Descriptions	Supported Device
ISPSoft [V3]	Free	PLC programming software	AS Series, AH Series, DVP Series
COMMGR [V1]	Free	Communication management software	AS Series, AH Series, DVP Series
DCISoft [V1]	Free	Ethernet configuration software	AH series Ethernet/serial communication modules, AS series SCM module, DVP series built-in Ethernet PLCs, DVP series Ethernet/serial communication modules, IFD series Ethernet modules
	Free	SCM serial communication module planning software	AS Series, AH Series, DVP Series SCM communication modules
CANopen Builder [V5]	Free	CANopen configuration software/motion control programming software	AS Series, AH Series, DVP Series built-in CANopen communication modules
EIP Builder [V1]	Free	EtherNet/IP configuration software	AS Series, AH Series, DVP Series built-in Ethernet communication modules
Delta OPC [V2] (HASP-20-OPC01)	Hardware License (USB)	Delta OPC Server	AS Series, AH Series,

■ Power Supply Module

Name	Model	Input	Output	Certification
Power Supply Module	AS-PS02	100~240 V _{AC}	24 V _{DC} , 2A (for modules on the rack)	CE/UL
	AS-PS02A		24 V _{DC} , 1.5A (for modules on the rack) 24 V _{DC} , 0.5A (for external I/O)	

Ordering Information

■ Communication Module

Name	Model	Communication Card Installation	Power Consumption (Internal)	Specifications	Certification
Communication Extension Module	AS00SCM-A	2	0.6 W	- Serial communication: RS-232/RS-422/RS-485 - Provide CANopen communication interface for extension racks	CE/UL
DeviceNet Communication Module	New AS01DNET-A	-	0.8 W	- DeviceNet protocol - Supports master/slave modes - Supports RTU function	

■ Digital I/O Module

Name	Model	I/O	Signals	Terminal Block Type	Power Consumption (Internal)	Certification
Input Module	AS08AM10N-A	8	24 V _{DC} 5 mA	Removable terminal block	0.72 W	CE/UL
	AS16AM10N-A	16			0.72 W	
	AS32AM10N-A	32		MIL	0.48 W	
	AS64AM10N-A	64			0.72 W	

Name	Model	I/O	Signals	Terminal Block Type	Power Consumption (Internal)	Specifications	Certification
Output Module	AS08AN01R-A	8	240 V _{AC} 24 V _{DC}	Removable terminal block	1.7 W	Relay	CE/UL
	AS16AN01R-A	16			3.4 W	Relay	
	AS08AN01T-A	8	5~30 V _{DC} 0.5A		0.72 W	Transistor NPN (Sink)	
	AS08AN01P-A	8			1.4 W	Transistor PNP (Source)	
	AS16AN01T-A	16			1.4 W	Transistor NPN (Sink)	
	AS16AN01P-A	16			1.4 W	Transistor PNP (Source)	
	AS32AN02T-A	32	5~30 V _{DC} 0.1A	MIL	0.72 W	Transistor NPN (Sink)	
	AS64AN02T-A	64			1.44 W	Transistor NPN (Sink)	

Name	Model	I/O	Signals		Terminal Block Type	Power Consumption (Internal)	Specifications	Certification
			Input	Output				
Input/Output Module	AS16AP11R-A	16 (8 in/8 out)	24 V _{DC} 5 mA	240 V _{AC} 24 V _{DC} 2A	Removable terminal block	1.9 W	Relay	CE/UL
	AS16AP11T-A	16 (8 in/8 out)		5~30 V _{DC} 0.5A		0.7 W	Transistor NPN (Sink)	
	AS16AP11P-A	16 (8 in/8 out)				0.7 W	Transistor PNP (Source)	

■ Analog I/O Module

Name	Model	Channel	Mode	Terminal Block Type	Power Consumption (Internal)	Specifications	Certification
Analog Input Module	AS04AD-A	4	1~5V 0~5V -5~5V 0~10V -10~10V 4~20mA 0~20mA -20~20mA	Removable terminal block	1.2W/2.5W	• Hardware resolution: 16-bit • Single channel on/off setting to enhance overall conversion efficiency • Conversion time: 2ms/channel • Wire break detection at 1~5V, 4~20mA modes	CE/UL
	New AS08AD-B	8	1~5V 0~5V -5~5V 0~10V -10~10V				
	New AS08AD-C		4~20mA 0~20mA -20~20mA				
Analog Output Module	AS04DA-A	4	0~10V -10~10V 4~20mA 0~20mA	Removable terminal block	1.2W/3W	• Hardware resolution: 12-bit • Single channel on/off setting • Conversion time: 250µs/channel	
Analog Input/Output Module	AS06XA-A	Input: 4 Output: 2	• Input: 1~5V 0~5V -5~5V 0~10V -10~10V 4~20mA 0~20mA -20~20mA • Output: 0~10V -10~10V 4~20mA 0~20mA		1.2W/2.5W	• Input resolution: 16-bit • Output resolution: 12-bit • Single channel on/off setting to enhance overall conversion efficiency • Conversion time: 2ms/channel • Wire break detection at 1~5V, 4~20mA modes	

Ordering Information

■ Temperature Measurement Module

Name	Model	Channel	Mode	Terminal Block Type	Power Consumption (Internal)	Specifications	Certification
RTD Temperature Measurement Module	AS04RTD-A	4	Pt100 Ni100 Pt1000 Ni1000 JPt100 LG-Ni1000 Cu50 Cu100	Removable terminal block	2W/1W	• Resolution 0.1°C/0.1°F • Conversion time: 200 ms/channel • Overall accuracy RTD: ±0.1% TC: ±0.5% • Wire break detection • Module monitoring, setting	CE/UL
	New AS06RTD-A	6	Input Impedence 0~300Ω 0~3,000Ω				
Thermocouple Temperature Measurement Module	AS04TC-A	4	J,K,R,S, T,E,N,B -100~+100mV				
	New AS08TC-A	8					

■ Load Cell Module

Name	Model	Channel	Mode	Terminal Block Type	Power Consumption (Internal)	Specifications	Certification
Load Cell Module	AS02LC-A	2	0~1 0~2 0~4 0~6 0~20 0~40 0~80 mV/V	Removable terminal block	0.75W/3W	- Resolution: 24-bit for hardware (ADC), 32-bit for data output 4-wire/6-wire load cell sensor - Selectable signal input ranges - LCSoft software configuration - High-speed dynamic measurement 50/60 Hz active filtering	CE/UL

■ Pulse Unit Module

Name	Model	Channel	Power Consumption (Internal)	Specifications	Certification
Pulse Unit Module	New AS02PU-A ^(*)	2	1.5 W	• Differential • 200 kHz • Supports motion APIs	CE/UL
	New AS04PU-A ^(*)	4	1.5 W	• Open collector • 200 kHz • Supports motion APIs	

Note 1: Please contact our distributors for release date

■ Function Cards

Name	Model	Channel	Specifications	Certification
Communication Card	AS-F232	1	Serial COM, RS-232 interface, slave/host mode	CE
	AS-F422	1	Serial COM, RS-422 interface, slave/host mode	
	AS-F485	1	Serial COM, RS-485 interface, slave/host mode	
	AS-FCOPM	1	• CANopen port, support DS301, AS Series remote control or Delta servo motor control • Built-in switchable terminal resistor (120 Ω)	
	New AS-FEN02	1	Ethernet port, RJ45 x2 (Switch function), supports EtherNet/IP (Adapter mode)/Modbus TCP	
	New AS-FPFN02 ^(*)	1	PROFINET port, RJ45 x2 (Switch function), supports PROFINET (Slave mode)	
Analog I/O Card	AS-F2AD	2	2-channel analog input 0~10 V (12-bit resolution), 4~20 mA (11-bit resolution), conversion time: 3 ms/channel	
	AS-F2DA	2	2-channel analog Output 0~10 V, 4~20 mA (12-bit resolution), conversion time: 2 ms/channel	

Note 1: Please contact our distributors for release date

Ordering Information

■ Accessories

Name	Model	Descriptions	Specifications		Applicable Module
			Length	Connector/ Terminal Block Type	
I/O Cable	UC-ET010-24B	I/O cable for connecting I/O modules and external terminal modules	1 m	I/O extension cable (MIL connector IDC40 to IDC40) (Shielded)	AS32AM,AS64AM, AS32AN,AS64AN
	UC-ET010-24D		1 m	I/O extension cable (MIL connector IDC40 to IDC20 x2) (Shielded)	AS332T,AS332P, AS324MT,AS32AM, AS64AM,AS32AN, AS64AN
	UC-ET020-24B		2 m	I/O extension cable (MIL connector IDC40 to IDC40) (Shielded)	AS32AM,AS64AM, AS32AN,AS64AN
	UC-ET020-24D		2 m	I/O extension cable (MIL connector IDC40 to IDC20 x2) (Shielded)	AS332T,AS332P, AS324MT,AS32AM, AS64AM,AS32AN, AS64AN
	UC-ET030-24B		3 m	I/O extension cable (MIL connector IDC40 to IDC40) (Shielded)	AS32AM,AS64AM, AS32AN,AS64AN
	UC-ET030-24D		3 m	I/O extension cable (MIL connector IDC40 to IDC20 x2) (Shielded)	AS332T,AS332P, AS324MT,AS32AM, AS64AM,AS32AN, AS64AN
Cables	UC-DN01Z-01A ^(*)	CANopen / DeviceNet cables	305.0 m	Thick / Trunk Cable	AS200 CPU, AS01DNET-A TAP-CN01, TAP-CN02, TAP-CN03
	UC-DN01Z-02A ^(*)		305.0 m	Thin / Drop Cable	
	UC-CMC003-01A	CANopen / DeviceNet / DMCNET cables	0.3 m	RJ45	AS-FCOPM TAP-CN03
	UC-CMC005-01A		0.5 m	RJ45	
	UC-CMC010-01A		1.0 m	RJ45	
	UC-CMC015-01A		1.5 m	RJ45	
	UC-CMC020-01A		2.0 m	RJ45	
	UC-CMC030-01A		3.0 m	RJ45	
	UC-CMC050-01A		5.0 m	RJ45	
	UC-CMC100-01A		10.0 m	RJ45	
	UC-CMC200-01A		20.0 m	RJ45	

Note:

- Ordering unit: meter
- Not available in Taiwan

■ Accessories

Name	Model	Descriptions	Specifications		Applicable Module
			Length	Connector / Terminal Block Type	
External terminal module	UB-10-ID16A	External terminal module of digital module	--	16 inputs or outputs (MIL connector, 20Pin)	AS332T, AS332P, AS324MT, AS32AM, 64AM,AS32AN, AS64AN
	UB-10-ID32A			32 inputs (MIL connector, 40Pin)	AS32AM, AS64AM
	UB-10-OT32A			32 transistor outputs (MIL connector, for NPN output)	AS32AN, AS64AN
	UB-10-OR16A			16 relay outputs (MIL connector, for NPN output)	AS332T, AS32AN02T, AS64AN02T
	UB-10-OR16B			16 relay outputs (MIL connector, for PNP output)	AS332P
	UB-10-IO32D			Connector converter (MIL→Spring)	AS332T, AS332P, AS324MT, AS32AM, AS32AN
Terminal resistors	TAP-TR01	CANopen/DeviceNet terminal resistors (RJ45)			
Distribution box	TAP-CP01	CANopen/ DeviceNet distribution Box	--	Power distribution box	
	TAP-CN01		--	1 for 2	
	TAP-CN02		--	1 for 4	
	TAP-CN03		--	1 for 4 (RJ45)	
Auxiliary Connected Power Module	AS-ATXB	Move the CPU power connector from left side to bottom side			
PLC programming cable	UC-PRG015-01A	Communication cable for PLC to PC	1.5m	PLC (mini USB)	All AS series CPU modules
	UC-PRG030-01A		3m	PLC (mini USB)	
	UC-PRG030-20A	Communication cable for PLC/ HMI (RJ45) to PC	3m	PLC/HMI (RJ45)	

■ Starter Kit

Name	Model	Specifications
Delta PLC starter kit	UT-AS332-C	AS332T-A CPU, power module and other accessories



Smarter. Greener. Together.

Industrial Automation Headquarters

Delta Electronics, Inc.

Taoyuan Technology Center
No.18, Xinglong Rd., Taoyuan District,
Taoyuan City 33068, Taiwan
TEL: 886-3-362-6301 / FAX: 886-3-371-6301

Asia

Delta Electronics (Shanghai) Co., Ltd.

No.182 Minyu Rd., Pudong Shanghai, P.R.C.
Post code : 201209
TEL: 86-21-6872-3988 / FAX: 86-21-6872-3996
Customer Service: 400-820-9595

Delta Electronics (Japan), Inc.

Tokyo Office
Industrial Automation Sales Department
2-1-14 Shibadaimon, Minato-ku
Tokyo, Japan 105-0012
TEL: 81-3-5733-1155 / FAX: 81-3-5733-1255

Delta Electronics (Korea), Inc.

Seoul Office
1511, 219, Gasan Digital 1-Ro., Geumcheon-gu,
Seoul, 08501 South Korea
TEL: 82-2-515-5305 / FAX: 82-2-515-5302

Delta Energy Systems (Singapore) Pte Ltd.

4 Kaki Bukit Avenue 1, #05-04, Singapore 417939
TEL: 65-6747-5155 / FAX: 65-6744-9228

Delta Electronics (India) Pvt. Ltd.

Plot No.43, Sector 35, HSIIDC Gurgaon,
PIN 122001, Haryana, India
TEL: 91-124-4874900 / FAX : 91-124-4874945

Delta Electronics (Thailand) PCL.

909 Soi 9, Moo 4, Bangpoo Industrial Estate (E.P.Z),
Pattana 1 Rd., T.Phraksa, A.Muang,
Samutprakarn 10280, Thailand
TEL: 66-2709-2800 / FAX : 662-709-2827

Delta Energy Systems (Australia) Pty Ltd.

Unit 20-21/45 Normanby Rd., Notting Hill Vic 3168, Australia
TEL: 61-3-9543-3720

Americas

Delta Electronics (Americas) Ltd.

Raleigh Office
P.O. Box 12173, 5101 Davis Drive,
Research Triangle Park, NC 27709, U.S.A.
TEL: 1-919-767-3813 / FAX: 1-919-767-3969

Delta Greentech (Brasil) S/A

São Paulo Office
Rua Itapeva, 26 – 3º Andar - Bela Vista
CEP: 01332-000 – São Paulo – SP - Brasil
TEL: 55-11-3530-8642 / 55-11-3530-8640

Delta Electronics International Mexico S.A. de C.V.

Mexico Office
Vía Dr. Gustavo Baz No. 2160, Colonia La Loma,
54060 Tlalnepantla Estado de Mexico
TEL: 52-55-2628-3015 #3050/3052

DISTRIBUIDOR DELTA BRASIL

KALATEC AUTOMACAO

WWW.KALATEC.COM.BR

19-3045-4900

EMEA

Headquarters: Delta Electronics (Netherlands) B.V.

Sales: Sales.IA.EMEA@deltaww.com
Marketing: Marketing.IA.EMEA@deltaww.com
Technical Support: iatechnicalsupport@deltaww.com
Customer Support: Customer-Support@deltaww.com
Service: Service.IA.emea@deltaww.com
TEL: +31(0)40 800 3800

BENELUX: Delta Electronics (Netherlands) B.V.

De Witbogt 20, 5652 AG Eindhoven, The Netherlands
Mail: Sales.IA.Benelux@deltaww.com
TEL: +31(0)40 800 3800

DACH: Delta Electronics (Netherlands) B.V.

Coesterweg 45, D-59494 Soest, Germany
Mail: Sales.IA.DACH@deltaww.com
TEL: +49(0)2921 987 0

France: Delta Electronics (France) S.A.

ZI du bois Challand 2, 15 rue des Pyrénées,
Lisses, 91090 Evry Cedex, France
Mail: Sales.IA.FR@deltaww.com
TEL: +33(0)1 69 77 82 60

Iberia: Delta Electronics Solutions (Spain) S.L.U

Ctra. De Villaverde a Vallecas, 265 1º Dcha Ed.
Hormigueras – P.I. de Vallecas 28031 Madrid
TEL: +34(0)91 223 74 20

C/Llull, 321-329 (Edifici CINC) | 22@Barcelona, 08019 Barcelona

Mail: Sales.IA.Iberia@deltaww.com
TEL: +34 93 303 00 60

Italy: Delta Electronics (Italy) S.r.l.

Ufficio di Milano Via Senigallia 18/2 20161 Milano (MI)
Piazza Grazioli 18 00186 Roma Italy
Mail: Sales.IA.Italy@deltaww.com
TEL: +39 02 64672538

Russia: Delta Energy System LLC

Vereyskaya Plaza II, office 112 Vereyskaya str.
17 121357 Moscow Russia
Mail: Sales.IA.RU@deltaww.com
TEL: +7 495 644 3240

Turkey: Delta Greentech Elektronik San. Ltd. Sti. (Turkey)

Şerifali Mah. Hendem Cad. Kule Sok. No:16-A
34775 Ümraniye – İstanbul
Mail: Sales.IA.Turkey@deltaww.com
TEL: + 90 216 499 9910

GCC: Delta Energy Systems AG (Dubai BR)

P.O. Box 185668, Gate 7, 3rd Floor, Hamarain Centre
Dubai, United Arab Emirates
Mail: Sales.IA.MEA@deltaww.com
TEL: +971(0)4 2690148

Egypt + North Africa: Delta Electronics

511 Cairo Business Plaza, North 90 street,
New Cairo, Cairo, Egypt
Mail: Sales.IA.MEA@deltaww.com