







A

Input



Ratio	12: 1	15: 1	16: 1	20: 1	25: 1	28: 1	30: 1	35: 1	40: 1	50: 1		70: 1		100: 1	未注公差							WPF115双段减速机				WPF115-L2shape drawing								
Nominal Output torque	230Nm	260Nm	230Nm	260Nm	260Nm	230Nm	125Nm	260Nm	230Nm	260Nm		90Nm		70Nm	0.5-3	±0.1																		
															3-6	±0.1																		
Allowable Axle force	1000N		IP level		IP65		Lubrication		Synthetic Lubrication oils		E21320				6-30	±0.2	标记	处数	分区	更改文件号	签名	年、月、日	视角											
Allowable radial force	1240N		Service life		20000h*		Torsional rigidity		11Nm/arcmin						30-120	±0.3	设计				标准化				阶段标记	重量	比例							
Nominal input speed	3500rpm		Mounting position		Any directions		Efficiency		93%						120-400	±0.5	校对				批准							1:1						
Backlash	P2≤12arcmin																审核																	
Noise	≤68dB		Operating Temp		-10℃~80℃														工艺							共	张	第	张	2018-9-7				
															轴套-Φ22xΦ24-(50310011)C																			

* 连续使用寿命 10000h